

SL-150

SL-150 panels feature a 1 1/2" leg height and continuous interlock. Concealed clip system for no exposed fastening while allowing for proper thermal expansion/contraction.

Key Features:

- Continuous Positive Lock
- No Exposed Fasteners
- Optional Stiffening Ribs
- Over 50 Standard Colors
- 20 or 30 year Finish warranty
- Custom Widths Available

Material Options

- Coil coated Steel
- Coil coated Aluminum
- Architectural Grade Sheet Copper
- Anodized Aluminum
- Mill Finish Aluminum

Fabrication Options

Steel	24ga
Aluminum032
Copper	16oz.
Minimum Length	36"
Maximum Length	80'

Finish Options

Painting

Kynar 500 / Hylar 5000, modified polyesters, and other custom or exotic finishes can be coil coated.

Anodizing

Clears, bronzes, and various other colors can be coil anodized for color consistency.

Custom Colors

We can provide full custom color services to match practically any material, shade, or tint you request.

Technical Data

- UL 2218 Class 4 Hail Rating
- ASTM E330-90 Structural Performance Testing
- ASTM E283-84 Air Infiltration Test
- ASTM E331-86 Water Penetration Test
- ASTM E1592-98 Uniform Static Air
- PA125 (UL90) Miami-Dade County Product Approved

