

# SL-175

SL-175 Panels feature architectural panel aesthetics with structural panel performance. A 1 3/4" seam height and continuous interlock.

## Key Features:

- Continuous Positive Lock
- No Exposed Fasteners
- Optional Stiffening Ribs
- Over 50 Standard Colors
- 20 or 30 year Finish warranty
- Custom Widths Available

## Material Options

- Coil coated Steel
- Coil coated Aluminum
- Anodized Aluminum
- Mill Finish Aluminum

## Fabrication Options

- Steel ..... 24ga
- Aluminum ..... .032
- Minimum Length ..... 36"
- Maximum Length ..... 80'

## Technical Data

- UL 2218 Class 4 Hail Rating
- ASTM E330-90 Structural Performance Testing
- ASTM E283-91 Air Infiltration Test
- ASTM E331-86 Water Penetration Test
- ASTM E1592-98 Uniform Static Air
- PA125 (UL90) Miami-Dade County Product Approved

## Finish Options

### Painting

Kynar 500 / Hylar 5000, modified polyesters, and other custom or exotic finishes can be coil coated.

### Anodizing

Clears, bronzes, and various other colors can be coil anodized for color consistency.

### Custom Colors

We can provide full custom color services to match practically any material, shade, or tint you request.

